

Overview

Product information

**Relay base-DPYF08A-3-00A(H)-30020000045**

DPYFrelay base,used for2PDYrelay,screw connection

Product advantages

- ✓ Plug-in relay socket
- ✓ Safe isolation between coil and contacts
- ✓ 10A, 2PDTgrade
- ✓ Arc partition between adjacent columns

Product certification

Technical data

Product drawing

3D model

☐

Environmental data

Ambient temperature (operation)

-40~+65℃

Ambient temperature (storage / transport)

-40~+65℃

Technical data

Rated voltage UN

300V

Rated current IN

7A

Installation location

Arbitrary

Assembly instructions

DIN35 rail

Connection data 1

Connection name

enter

Connection method	Screw connection
Stripping length	7-8mm
screw thread	M3
Cross section of flexible conductor	0.5... 2.5mm ²
Connectable guide cross section AWG	20-14AWG

Connection data 2

Connection name	Output
Stripping length	7-8mm
Cross section of flexible conductor	0.5... 2.5mm ²
Connectable guide cross section AWG	20-14AWG
Connection method	Screw connection

Dimension

length	76.5mm
width	22mm
Depth including bracket	31mm

Accessories

Business data

Order number	30020000045
Packing unit	
Minimum order quantity	
Products weight (without packaging)	